

PARKING BRAKE COMPRISING MECHANISM FOR ADJUSTING BRAKE CABLE TENSION

FIELD OF THE INVENTION

5 The present invention relates to a parking brake of a vehicle. Specifically, the invention is directed to a parking brake wherein the cable tension is automatically adjusted to be maintained as a predetermined level even if the brake cable is loosen due to frequent operations.

10 BACKGROUND OF THE INVENTION

 In general, a vehicle has a foot brake for braking operation during driving and a parking brake for braking operation when the vehicle is parked. The parking brake lever is operated by a hand generally. Pulling the lever pulls a brake cable to carry braking operation.

15 Frequent braking operations may loose the brake cable. It causes insufficient tension, thereby reducing braking force. Even fully pulling the parking brake lever cannot perform braking operation properly. In this circumstance, the vehicle should be fixed so that the cable length is adjusted by a repairman.

 Many devices for automatically adjusting the brake cable tension has been
20 developed.

 For example, US Patent Nos. 5,272,935 and 6,382,048 disclose the devices for automatically adjusting the brake cable tension. The techniques of the patents employs elastic member such as spring for automatically adjusting the brake cable tension. However, the structure of the devices is complex and is not easy to repair or assemble
25 because of a lot of components.

SUMMARY OF THE INVENTION

The object of the present invention is to provide a parking brake comprising mechanism for automatically adjusting brake cable tension, which has less components and is easier to assemble than the conventional arts.

5 A parking brake of a vehicle according to one embodiment of the invention comprises a supporting member adapted to be fixed to a frame of the vehicle and provided with a ratchet portion; a parking brake lever mounted on the supporting member and oscillatable between a braked position and a released position; a braking pawl oscillatably mounted on the parking brake lever and engaging with the ratchet
10 portion to prevent the parking brake lever from oscillating when the parking brake lever is in its braked position; a toothed member having a first toothed segment and a second toothed segment and oscillatably mounted on the parking brake lever; a tension-adjusting pawl adapted to engage with the first toothed segment and oscillatably mounted on the parking brake lever; a position-locking pawl adapted to engage with the
15 second toothed segment and having a guided member; a spool having a cable fixing portion where a parking brake cable is fixed and fixed to the toothed member; and a guiding means having a first guiding segment and a second guiding segment along which the guided member of the position-locking pawl is guided.

 The position-locking pawl is oscillatably mounted on the supporting member.
20 The guided member is guided along the first guiding segment while the parking brake lever oscillates over a predetermined degree from the released position.

 The position-locking pawl engages with the second toothed segment to prevent the toothed member and the spool from rotating while the guided member is guided along the first guiding segment during oscillation of the parking brake lever to the
25 released position from the braked position.

 The parking brake may further comprise a first biasing means for biasing the

tension-adjusting pawl toward the first toothed segment and a second biasing means for biasing the position-locking pawl toward the second toothed segment.

It is preferred that the guiding means is guiding surface formed in the parking brake lever.

5 It is also preferred that the first toothed segment is formed so that the tension-adjusting pawl moves along the segment while the position-locking pawl engages with the second toothed segment during oscillation of the parking brake lever to the released position from the braked position.

10 It is further preferred that the guided member is a pin mounted on said position-locking pawl.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated into and form a part of the specification, illustrate several embodiments of the present invention and, together with
15 the description, serve to explain the principles of the invention. The drawings are only for the purpose of illustrating preferred embodiments of the invention and are not to be construed as limiting the invention. In the drawings:

Fig. 1 shows a side view of a parking brake according to the invention;

20 Fig. 2 shows a side view of the parking brake of the invention where a brake cable tension adjusting mechanism is provided;

Fig. 3 shows a side view of the parking brake wherein the brake lever is pulled toward to braking position;

25 Fig. 4 shows a side view of the parking brake wherein the brake lever is pulled as much as critical degree since the brake cable length increases more than a predetermined amount;

Fig. 5 shows a side view of the parking brake wherein the brake lever is more

pulled from the critical position shown in Fig. 4;

Fig. 6 shows a side view of the parking brake wherein the brake lever returns to releasing position from the position shown in Fig. 5;

Fig. 7 shows a side view of the parking brake wherein the brake lever returns to
5 a complete releasing position;

Fig. 8 shows a partial bottom view of the parking brake;

Fig. 9 shows a partial plan view of the parking brake;

Fig. 10 shows a side view of a parking brake of another embodiment in normal state; and

10 Fig. 11 shows a side view of the parking brake shown in Fig. 10 wherein the parking brake lever is in braking position.

DETAILED DESCRIPTION OF THE INVENTION

As shown in Fig. 1, a parking brake 1 according to one embodiment of the
15 invention comprises a supporting member 10 having a ratchet portion 15 formed therein, a parking brake lever 20 pivotably mounted in supporting member 10, an operating rod 30, a braking pawl 40 pivotably mounted in parking brake lever 20, a push button 31 provided in one end of operating rod 30. Parking brake lever 20 is pivotable with respect to axis 11. Braking pawl 40 is fixed in operating rod 30 with pin
20 12 and is pivotable with respect to axis 13. Parking brake 1 further comprises a spring 33. One end of spring 33 is fixed to push button 31 and the other end of the spring is fixed to a stopper 35.

Parking brake lever 20 is pulled clockwise for braking, thereby moving braking pawl 40 to engage with ratchet portion 15 of supporting member. Pulling brake lever 20
25 results in pulling brake cable wound in spool 2. The braked position can be maintained since braking pawl 40 engages with ratchet portion 15.

For releasing, push button 31 is pushed, thereby releasing the engagement between braking pawl 40 and ratchet portion 15. Thereafter, parking brake lever 20 is oscillated to a normal position.

Figs. 2 to 7 show the other side of parking brake 1. In this side, provided is a mechanism for automatically adjusting brake cable tension.

As shown in Fig. 2, the mechanism for automatically adjusting brake cable tension comprises a spool 2, a toothed member 3, a tension-adjusting pawl 5, a position-locking pawl 6, a guide means 100, a first biasing means 7 and a second biasing means 8.

Toothed member 3 comprises a first toothed segment 3a and a second toothed segment 3b.

Spool 2 comprises cable fixing portion 9a for fixing parking brake cable 9, winding groove 2a for winding brake cable 9. The spool is mounted in parking brake lever 20 so as to be pivotably with respect to axis 4. In the embodiment, toothed member 3 and spool 2 are formed separately and thereafter are engaged each other with fixing means 60a, 60b. Alternatively, they are formed integrally.

It is shown in Fig. 2 that the pitch of first toothed segment 3a is larger than that of second toothed segment 3b. However, the pitch of first toothed segment 3a may not be larger than that of second toothed segment 3b.

Tension-adjusting pawl 5 is engageable with first toothed segment 3a of toothed member 3 and is biased toward first toothed segment 3a by first biasing means 7. When tension-adjusting pawl 5 engages with first toothed segment 3a, toothed member 3 and spool 2 oscillates together with parking brake lever 2.

Position-locking pawl 6 is engageable with second toothed segment 3b, with not engaging with the segment in releasing position which is initial state. Position-locking pawl 6 is also biased toward second toothed segment 3b by second biasing

means 8. Further, position-locking pawl 6 is pivotable, centering around axis 6a, with respect to supporting member 10. Position-locking pawl 6 comprises a guided member 65 that is guided along guiding means 100. It is preferred that guided member 65 is pin which is provided in position-locking pawl 6.

5 The rotation of toothed member 3 of spool 2 is prevented even when parking brake lever 20 is oscillated toward released position, while position-locking pawl 6 engages with second toothed segment 3b. First toothed segment 3a is formed as shown in Fig. 2 so that tension-adjusting pawl 5 moves along first toothed segment 3a while the rotation of toothed member 3 is prevented.

10 It is preferred that first biasing means 7 and second biasing means 8 are plate spring as shown in Fig. 2.

 Guiding means 100 comprises first guiding segment 100a and second guiding segment 100b. It is preferred that the guiding segments are formed as curved surfaces in one lateral side of parking brake lever 20. Alternatively, guiding means 100 may be
15 provided with use of an additional member and this also falls within the scope of the invention.

 Guided member 65 is guided along second guiding segment 100b when parking brake lever 20 oscillated to braked position from released position until the member reaches a predetermined point A. If parking brake lever 20 is pulled even after the
20 member 65 reaches the point A, guided member 65 is guided along first guiding segment 100a.

 While guided member 65 is guided along second guiding segment 100b, position-locking pawl 6 does not engage with second toothed segment 3b. While guided member 65 is guided along first guiding segment 100a, position-locking pawl 6
25 engages with second toothed segment 3b.

 Parking brake cable 9 is wound in winding groove 2a with the end thereof being

fixed in fixing portion 9a of spool 2. Spool 2 rotates by pulling parking brake lever 20 to pull parking brake cable 9, thereby generating braking force.

Oscillating parking brake lever 20 in the direction of arrow “B” as shown in Fig. 3 causes guided member 65 to move along second guiding segment 100b. The oscillation of the lever also causes spool 2 to rotate, thereby making position-locking pawl 6 closer to second toothed segment 3b. Unless parking brake cable 9 is loose as much as a predetermined level, braking is possible in the state shown in Fig. 3. Further, the mechanism for automatically adjusting cable tension does not operate since position-locking pawl 60 does not engage with second toothed segment 3b.

However, if parking brake cable 9 is loose over a predetermined level, parking brake lever 20 should be pulled farther as shown in Figs. 4 and 5 for proper braking. Fig. 4 shows a side view of the parking brake when guided member 65 of position-locking pawl 6 passes point A between first guiding segment 100a and second guiding segment 100b. Fig. 5 shows a side view of the parking brake when guided member 65 is guided along first guiding segment 100a due to more pulling of parking brake lever 20 compared with the state shown in Fig. 4. As described in the above, position-locking pawl 6 engages with second toothed segment 3b of toothed member 3 while guided member 65 is guided along first guiding segment 100a.

Guided member 65 starts to move along first guiding segment 100a, together with oscillation of parking brake lever 20 in the direction of arrow “C” as shown in Fig. 6 for releasing the braked condition. While guided member 65 moves along first guiding segment 100a, second toothed segment 3b of toothed member 3 engages with position-locking pawl 6, thereby preventing toothed member 3 and spool 2 from rotating. Thus, tension-adjusting pawl 5 moves along first toothed segment 3a as shown in Fig. 6.

In the complete released position as shown in Fig. 7, the engagement between

position-locking pawl 6 and second toothed segment 3b is released and guided member 65 contacts with second guiding segment 100b. In particular, tension-adjusting pawl 5 is shifted by a predetermined pitch along first toothed segment 3a from the initial position and engages with first toothed segment 3a. That is, spool 2 further winds parking brake cable as much as Δl , thereby compensating the loose length of the cable. Thus, the tension of the parking brake cable can be automatically adjusted without additional repair.

Fig. 10 shows a side view of a parking brake 1000 according to another embodiment of the invention. The parking brake 1000 is operated by foot, not hand.

Fig. 11 shows a side view of the parking brake in its braked position.

The parking brake 1000 differs from parking brake 1 in that a driver operates the parking brake with his/her foot pressing pedal 1500 provided in one end of parking brake lever 1020 counterclockwise. The elements of parking brake 100 which have the same function as those of parking brake 1 is described with the same reference numerals as the elements of parking brake 1.

As described for parking brake 1 in the above, if parking brake cable 9 is loose over a predetermined amount, guided member 65 is guided along first guiding segment 100a while parking brake lever 1020 is oscillated toward its braked position. While guided member 65 is guided along first guiding segment 100a when the parking brake lever is oscillated toward released position, position-locking pawl 6 is engaging with second toothed segment 3b. Since, in this state, the rotation of toothed member 3 and spool 2 is prevented due to the engagement between position-locking pawl 6 and second toothed segment 3b, tension-adjusting pawl 5 moves along first toothed segment 3a. When guided member 65 reaches second guiding segment 100b, the engagement between position-locking pawl 6 and second toothed segment 3b is released. Finally, tension-adjusting pawl 5 moves as much as a predetermined pitch along first toothed

segment 3a and engages with the segment. In this state, cable 9 is tightened as much as a predetermined amount as described in the above.

According to the invention, it is possible to adjust the parking brake cable tension automatically since the cable is further wound in the spool as much as extended
5 length. Further, the structure of the parking brake using guided member and guiding means becomes simple compared with the conventional art since it does not employ tension-adjusting mechanism using spring means.

The invention will now be described based on the preferred embodiments, which do not intend to limit the scope of the present invention, but exemplify the
10 invention. All of the features and the combinations thereof described in the embodiments are not necessarily essential to the invention.

Although the present invention has been described by way of exemplary embodiments, it should be understood that those skilled in the art might make many changes and substitutions without departing from the spirit and the scope of the present
15 invention which is defined only by the appended claims.